


# LABELSTOCK **TRUDIGITAL® JET HIGH GLOSS** 90/11F25/WG60





## Facestock

A super high gloss inkjet paper for high definition printing. Quick drying and suitable for most high-speed waterbased inkjet systems.

Basis weight (g/m²)	95	ISO 536
Caliper (µ)	106	ISO 534

## **Release liner**

A super calendared white glassine, silicone coated one side.

60	ISO 536
53	ISO 534
51	DIN 53147
	53

## **Conversion and Printing**

Specially formulated for use with all common commercial high-speed inkjet printing systems.

## Adhesive

11F25 is a deep freeze permanent sensitive adhesive (PSA). This adhesive should be used when very good adhesion to low temperatures is necessary. Adhesion to low energy surfaces is very good.

Loop Tack (N/25mm)	10	FINAT No 9 (glass)	
Peel adhesion (N/25mm)	10	FINAT No 1 (glass)	
Minimum application temp	-20°C		
Service temperature	-40°C to +60°C		

#### Regulatory approval:

The adhesive may stand in direct contact with dry, moist and such kind of fatty foodstuffs to which a correction factor of at least 4 can be applied according to the commission regulation (EU) No. 10/2011.

Furthermore, it may be safely used for the labelling of blood bags (DIN EN ISO 3826-1). The adhesive is compliant to FDA 175.105

#### **Our Warrantv**

Cur warranty The technical infonnation, recommendations and statements are based on data believed to be reliable but do not constitute a guarantee or warranty. The information is given without legal responsibility. The customer should test under own condition to ensure the product is suitable for their own requirements. Tullis Russell products are warranted to be free of defects in material for a period of up to one year from the date of shipment. Tullis Russell will not be responsible for claims beyond the replacement value of the defective product nor in any way be liable or responsible for consequential or incidental damages. No waiver, alteration, addition or modification of the foregoing conditions shall be valid unless made in writing and signed by a Director of Tullis Russell. Other warranty, express or implied, or whether of merchantability or fitness for a particular use or otherwise, shall be excluded. Shelf life: 12 months at 22<sup>°</sup>C and 50% RH.

